

## Most Trusted Traveling Irrigation Systems **Since 1964**

## Caprari Model D3/65 PTO Pump



- Compact, reliable PTO pump capable of 150 to 530 gpm with corresponding pressures of 161 to 131 psi using 29 to 59 hp
- Available with heavy duty two wheeled trailer or galvanized three point mount
- Designed with industry leading oil lubricated step up gearbox (no belts or pulleys) with shafts supported by widely spaced bearings
- Easily replaceable packing gland type water seal
- Pumps can be fitted with 4" female thread discharge priming valve, hand primer, fluid filled pressure gauge, short suction adapter with 4" female pipe thread and #6 heavy duty 1 3/8 six spline PTO shaft

O INPUT RPM \*\*

350

300 250 20 ± 5 10 W

173.4

151.7

130.1


108.4 ပ္ထ

86.7

65.0

43.4 60 <sup>40</sup> 호

| Technical Specifications        |  |
|---------------------------------|--|
| Discharge & Suction             | (Bare or Pump, Cart & Shaft) Flanged   |
| Discharge & Suction             | (Fully Fitted) 4" NPT (F)  |
| Discharge Position              | Horizontal, Right Facing (When Standing<br>Behind The Suction End)                                   |
| Length                          | 65 Inches  |
| Width                           | 48 Inches  |
| Height                          | 40 Inches  |
| Weight (Unfitted)               | 270 lbs.   |
| Weight (Fitted)                 | 330 lbs.   |
| Configurations                  |  |
| Bare Pump                       | Pump only with weld-on companion flanges, gaskets, nuts & bolts                                      |
| Pump, Cart & Shaft              | Same as bare pump, but mounted on two-<br>wheeled cart & PTO drive shaft                             |
| Fully Fitted                    | Sames as pump, cart & shaft plus hand<br>primer, check valve, pressure gauge and<br>suction fittings |
| Options (Additional Fees Apply) |  |
| Three-Point Hitch               | Fully galvanized frame may be substituted for cart   |
| Suction Hose                    | 4" x 30' Aquaflex  |
| Foot Valves & Strainers         | 4" Cast or Aluminum 45°  |
| Special Execution               | Consult Factory  |



## www.kifco.com



700 S. Schrader Ave. P.O. Box 290 Havana, IL 62644 800-452-7017 Toll Free 309-543-4425 Phone 309-543-4945 Fax www.kifco.com